




# SAHH BEARING OF ENGLAND CORP.



3.937 Inch | 100 Millimeter x 7.087 Inch | 180 Millimeter x 1.339 Inch | 34 Millimeter 3.937 Inch | 100 Millimeter x 7.087 Inch | 180 Millimeter x 1.339 Inch | 34 Millimeter SKF NU 220 ECML/C3 Belgium Bearing 100 × 180 × 34

Bearing No. NU 220 ECML/C3

NU 220 ECML/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.878
EAN	7316570738629
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	100MM Bore; Straight Bore



## SAHH BEARING OF ENGLAND CORP.

	Profile; 180MM Outside Diameter; 34MM Width; Brass Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NU 220 ECML/C3
Weight / LBS	8.541
d	3.937 Inch   100 Millimeter
D	7.087 Inch   180 Millimeter
B	1.339 Inch   34 Millimeter
bore diameter:	100 mm
static load capacity:	305 kN
outside diameter:	180 mm
precision rating:	Not Rated
overall width:	34 mm
maximum rpm:	4550 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Ring
outer ring width:	34 mm



## SAHH BEARING OF ENGLAND CORP.

operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	285 kN
series:	NU2